



EPOCHEMMIE CO., LTD

www.epochemmie.com

E-mail: sales@epochemmie.com epochemmie@163.com

DATA SHEET

Commodity: ACTIVATED CARBON

Type: EP-I-S

EP-I-S : Pellet Coal based Activated carbon, Impregnated Sulphur, largely used to remove mercury in natural gas treatment, air treatment, hydrogen treatment and so on.

Distinguishing feature:

- (1) Sulphur impregnated, for remove mercury in gas applications
- (2) High Adsorption Capacity & Surface Area
- (3) High developed and reasonable pore structure

Application

EP-I-S coal based Sulphur impregnated activated carbons are produced from naturally excellent quality anthracite coal with low ash, low sulphur and very low water soluble material.

And it is specially designed to remove mercury in natural gas treatment, air treatment, hydrogen treatment and so on.

Product Specifications:

ITEM/TYPE	EP-I-KI60
Sulphur impregnated content %	10-15% or as per request
CTC Adsorption %	60
Hardness % min	95
Moisture % max (as packed)	5
Bulk Density g/l	530-560
Particle size 90%min passed	4.0mm

Packing: 25kg bag, 500kg jumbo bag or pallet packing or as per customer's requirement

Inspection standard: the above specification is based on Chinese Government standard GB

And customer can also inspect as per American ASTM standard.

Safety

Wet activated carbon depletes oxygen from air and, therefore, dangerously low levels of oxygen maybe encountered. Whenever workers enter a vessel containing activated carbon, the vessel's oxygen content should be determined and work procedures for potentially low oxygen areas should be followed. Appropriate protective equipment should be worn. Avoid inhalation of excessive carbon dust. No problems are known to be associated in handling this material. However, dust may contain greater than 1.0% silica (quartz). Long-term inhalation of high dust concentrations can lead to respiratory impairment. Use forced ventilation or a dust mask when necessary for protection against airborne dust exposure.